

Marine Travelift
Forklift Brochure 2016

Production Notes: Do not print!

These production notes are on separate layer in InDesign.
Please turn off before outputting.

Art set up as reader spreads. First spread shows front and back covers.

Flat Size: 17" x 11"

Folded Size: 8.5" x 11"

Page count: 8 pages - including cover

Prints: 4 color process and aqueous throughout with full bleeds.

Please verify with Marine Travelift on choice of matte or gloss aqueous.

Score for fold, collate, staple bind, box, and deliver.

Paper Stock: 80# White Coated 2 side Premium Cover (recommended only)

Final art provided in InDesign CC 2015 along with supporting Photoshop and Illustrator files and FONTS. An idml file is also provided if needed for lower versions of InDesign.

MARINE  TRAVELIFT®

Trusted Name, Proven Value

49 E Yew Street
Sturgeon Bay, WI 54235 USA

marinetralevift.com

sales@marinetralevift.com

Phone: +1.920.743.6202

Fax: +1.920.743.1522

Information contained within this brochure is believed to be correct at time of printing. Not all accessories shown in photos or described may be available as standard equipment or as an option. Options, features and specifications are subject to change without notice.



MARINE FORKLIFTS

Higher efficiency.
Proven durability.



Marinas and boat yards are proving grounds for efficiency and durability.



M2800 - Florida, USA

After more than 25 years designing, building and supporting our complete line of forklifts, Marine Travelift machines continue to surpass the rest.

Nonstop lifting and hauling from sunup to sundown. Endless exposure to the elements. Your marina's productivity relies on dependable forklifts, so you can operate with greater versatility every day and withstand harsh marine conditions for years to come.

Our marine forklifts are built around an easy to control hydrostatic drive to help you meet these challenges head on. Reinforced with powerful swing style forks and all-around corrosion resistance, our forklifts deliver the continued productivity your yard demands.

Solutions that keep your machines working hard.

Our priority is to meet or exceed your specifications using the highest safety and performance standards. So whatever you need to lift, your machine will perform with best-in-class efficiency, durability and versatility.

From design to delivery and beyond, our team of engineers, technicians and industry experts helps to ensure your machine performs at its best, day in and day out.

- **Genuine Marine Travelift replacement parts** are made specifically to match the original specifications of your machine
- **Local support** works directly with our team to diagnose and coordinate repairs and minimize downtime
- **Experienced factory-trained technicians** are ready to be dispatched for on-site analysis and repairs
- **In-house technical support** will work with you and your local dealer to find solutions that keep your machine functioning at peak performance



M2500 - Doha, Qatar



M2000 - Denia, Spain

Marine Forklifts

MODEL	CAPACITY
M1500	15,000 lbs. / 7,000 kg
M2000	20,000 lbs. / 9,000 kg
M2000S	20,000 lbs. / 9,000 kg
M2300	20,000 lbs. / 9,000 kg
M2500	25,000 lbs. / 11,000 kg
M2800	27,000 lbs. / 12,000 kg

And more...

Visit marinetraavelift.com to see product videos of our forklifts in action, as well as a current list of available features and options.



Taking usability and productivity to the next level.

We design every forklift for ease of use without compromising its capabilities. Crafts big or small, hulls long or short – our forklifts deliver the performance your job demands with the usability and durability you expect from all Marine Travelift machines.

STANDARD FEATURES



FORWARD/SIDE MOUNTED CAB

More visibility and easy cab access from both sides of the machine.



CORROSION RESISTANCE

Prolong paint life and resist corrosion in harsh marine environments with our zinc primer and stainless steel tubing.



HYDROSTATIC DRIVE

Easily maintain precise speed and control in any direction while keeping hands free for steering, hydraulic lift controls and other pilot operations.



CONTROLS

Lift every load with greater precision and efficiency using electronic throttle and pilot operated hydraulic controls.



SWING STYLE FORKS

Improve fork positioning, versatility and boat handling control.



M1500



M2000



M2000S

OPTIONS



VARIOUS MAST HEIGHTS

Masts are available in a variety of heights to meet the needs of your yard.



SOLID NON-MARKING TIRES

Reduce downtime and maintenance while promoting a cleaner operation.



GALVANIZED CAB, CARRIAGE AND/OR FORKS

Additional corrosion protection for various parts of your machine.



MOLDED EXTRUSION RUBBER FORK COVER

Additional protection for your forks.



WIRELESS REMOTE CONTROLS

Raise and lower the forks while launching or retrieving boats.



SHORTER WHEEL BASE

Improve mobility and maneuverability in confined spaces with added control.



M2300



M2500



M2800

How to select the right marine forklift.

Model		M1500	M2000
Standard Lifting Height		32.8 ft. (10.0 m)	30 ft. (9.1 m)
Mast Height Collapsed		15.9 ft. (4.9 m)	21.7 ft. (6.6 m)
Negative Drop		10 ft. (3.0 m)	12 ft. (3.7 m)
Front Axle Load		72,700 lbs. (32,976 kg)	84,000 lbs. (38,102 kg)
Maximum Drive Speed		10.9 mph (17.5 km/h)	10.9 mph (17.5 km/h)
Lifting capacity when load is 4' from ground and boat center of gravity is:*	8 ft. (2.4 m)	15,000 lbs. (6,804 kg)	20,000 lbs. (9,072 kg)
	10 ft. (3.0 m)	12,900 lbs. (5,851 kg)	17,200 lbs. (7,802 kg)
	12 ft. (3.7 m)	11,250 lbs. (5,102 kg)	15,000 lbs. (6,804 kg)
	14 ft. (4.3 m)	10,050 lbs. (4,558 kg)	13,400 lbs. (6,079 kg)
	16 ft. (4.9 m)	9,000 lbs. (4,082 kg)	12,000 lbs. (5,444 kg)
	18 ft. (5.5 m)	8,250 lbs. (3,742 kg)	11,000 lbs. (4,990 kg)
Estimated minimum aisle space required for boat length of:	25 ft. (7.6 m)	43.5 ft. (13.3 m)	45.5 ft. (13.9 m)
	30 ft. (9.1 m)	48.5 ft. (14.8 m)	50.5 ft. (15.4 m)
	35 ft. (10.7 m)	53.5 ft. (16.3 m)	55.5 ft. (16.9 m)
	40 ft. (12.2 m)	58.5 ft. (17.8 m)	60.5 ft. (18.4 m)
	45 ft. (13.7 m)	63.5 ft. (19.4 m)	65.5 ft. (20.0 m)
	50 ft. (15.3 m)	68.5 ft. (20.9 m)	70.5 ft. (21.5 m)

*Greater lifting heights will result in lower lifting capacities. See the load charts on model specification sheets.



M1500 - Kragero, Norway



M2000 - Queensland, Australia

M2000S	M2300	M2500	M2800
30 ft. (9.1 m)	30 ft. (9.1 m)	40 ft. (12.2 m)	45 ft. (13.7 m)
21.7 ft. (6.6 m)	21.7 ft. (6.6 m)	19.7 ft. (6.0 m)	30.5 ft. (9.3 m)
12 ft. (3.7 m)	12 ft. (3.7 m)	12.7 ft. (3.9 m)	12 ft. (3.7 m)
91,900 lbs. (41,685 kg)	92,500 lbs. (41,957 kg)	102,900 lbs. (46,675 kg)	114,500 lbs. (51,936 kg)
10.9 mph (17.5 km/h)	10.9 mph (17.5 km/h)	9.5 mph (15.3 km/h)	8 mph (12.9 km/h)
20,000 lbs. (9,072 kg)	20,000 lbs. (9,072 kg)	25,000 lbs. (11,340 kg)	27,000 lbs. (12,247 kg)
17,200 lbs. (7,802 kg)	20,000 lbs. (9,072 kg)	21,500 lbs. (9,752 kg)	27,000 lbs. (12,247 kg)
15,000 lbs. (6,804 kg)	20,000 lbs. (9,072 kg)	18,750 lbs. (8,505 kg)	25,000 lbs. (11,340 kg)
13,400 lbs. (6,079 kg)	17,100 lbs. (7,756 kg)	16,750 lbs. (7,598 kg)	22,400 lbs. (10,161 kg)
12,000 lbs. (5,444 kg)	15,000 lbs. (6,804 kg)	15,250 lbs. (6,917 kg)	20,200 lbs. (9,163 kg)
11,000 lbs. (4,990 kg)	13,300 lbs. (6,033 kg)	13,750 lbs. (6,237 kg)	18,400 lbs. (8,346 kg)
44.5 ft. (13.6 m)	47 ft. (14.3 m)	46.5 ft. (14.2 m)	49.75 ft. (15.2 m)
49.5 ft. (15.1 m)	52 ft. (15.8 m)	51.5 ft. (15.7 m)	54.75 ft. (16.7 m)
54.5 ft. (16.6 m)	57 ft. (17.4 m)	56.5 ft. (17.2 m)	59.75 ft. (18.2 m)
59.5 ft. (18.1 m)	62 ft. (18.9 m)	61.5 ft. (18.7 m)	64.75 ft. (19.7 m)
64.5 ft. (19.7 m)	67 ft. (20.4 m)	66.5 ft. (20.3 m)	69.75 ft. (21.3 m)
69.5 ft. (21.2 m)	72 ft. (21.9 m)	71.5 ft. (21.8 m)	74.75 ft. (22.8 m)



M2000S - Florida, USA



M2800 - Florida, USA